Cirecò

Product spec sheet 48x40 Stackable Pallet


Features & Benefits

- Foam injection molded with compatibilized materials, providing superior durability, exceptional impact resistance, and optimized performance.
- Designed with an optimal footprint and 4-way entry, ensuring efficient trailer loading and full versatility in the warehouse and during delivery.
- Anti-slip edges designed for effortless loading.
- Designed for seamless automation, compatibility with conveyor systems, and stacking.
- Open design allows for easy washing and maintenance.
- Sustainable production utilizing 100% Green Circle Certified recycled plastic made from post-consumer materials. It is fully recyclable at the end of its life, enabling reuse and contributing to the Circular Plastic Economy.
- Designed for safe in-store display, ensuring product integrity and customer safety.
- The perimeter lip helps reduce product damage by securing items and minimizing unnecessary related costs.

Options

- Available in black only.
- Hot-stamped logos are available in various color options for customer-specific branding and can be applied on all four sides.
- RFID capability.
- Cost-effective leasing options are available.
- Exclusive buy-back recycling program provides exceptional value at the end of the product life cycle, promoting sustainability and supporting the Circular Plastic Economy.

NZN.		10 51	5.00 1				14.00	15.0	125.0	A Frie	
	Nº AL			10	172	8771	10. 24		0.00	2 3	18
314	11:4-5	100 54	LAN A	1. 1.	14.81	144	12. 14	17. 0	12.1		11
2 202	NUC 1	NV/		NZ4	WVZ	NU	NZ	W		7 117	7 10
					0.0	Z 60					
	ANN BOX										
N KAIN	J. ZEAN	ZŇ		ZN	MN	Zin	ZAN	17/1	NV/N	100	122
2 22 2	10.00	NZ		NZ4	1 1	N 15	NZ	NZ	2 11	2	2 85 1
N 161 A						2.0	ZA			NINE D	
1 83.4	1 1 1 2			NZ4	21	NE	NZ	W		2 1 2 7	2 2 2
12 10 11	10.101	12.1	1. 1.	19	11.10	01.11	125.2	08.7	0.012	2 101	9 M
N TAN	1.1 4 1	12 - 24	J	6.04	412	154	14. 18	Be a	10.1	144	11/4
19								0			
N 6200	100					2.8				100	\$ 60
10 10 10		NZ									
	104 W										
	N N P										
	. 42 M.										
2005	115.62										200
1 1 2 2 1				ΔN	MAN N	ZUN	M N			N ION	125
21.0	10.0	10.20	2.0	6 V.	Sec. 16.	N 22	1.6	1 1 1			
N ZAN	N. Carl	10.00	10 A			211		(Mar)	N MAR	Yax	18.1
		2027	\mathbf{v}		<u>1</u> 24		1. 10	QX 7	0.00		



Specifications and Capacities

Length = 48"

Width = 40"

Height = 6"

Dynamic load rating = 6,000 lbs. Static load rating = 30,000 lbs. Racking load rating = 1,491 lbs. Trailer QTY = 560

Weight = 52 lbs.